

# DX1 Hazardous Location Plugs & Receptacles – 20 A

Devices rated for hazardous locations are not returnable.

## Ratings

- **Max Amperage & Voltage**  
20 A, 750 VAC
- **Environmental Ratings**  
IP65
- **Temperature Range**  
Min -13°F / Max 140°F  
See pg 258 for temps below -15°F.
- **Wiring Capacity**  
Min 14 AWG Max 8 AWG  
\* Based on THHN wire sizes
- **Applicable Standards**  
ATEX, IECEx
- **Hazardous Location Ratings**

MARECHAL ELECTRIC MAROMME  
II2 G/D Ex de IIC tD A21  
-25°C ≤ Ta ≤ +60°C T5 T84°C  
-25°C ≤ Ta ≤ +50°C T6 T74°C  
IECEx LCI 09.0014/LCIE 05 ATEX 6127

## XXX Suffix / Cable Range

XXX (Suffix #)	Cable Range
-20M	.31" - .51"
-25M	.35" - .63"


## XX Suffix / NPT Size

NPT Thread Size	XX (Suffix #)
1/2"	-12
3/4"	-34
1"	-1

NPT sizes are determined by the cable diameter and third party cord grip.

## Accessories

### Protective Cap



For Male  
Devices Only

DX1 26-2A126

### Metal Wall Box



NPT	Part #
1/2"	26-2A023-12
3/4"	26-2A023-34
1"	26-2A023-1

## Plug (Male inlet w/handle)



## Inlet w/cap on box (Male)



or

## North American Configurations

Voltage	Polarity	Part #	
		Metal	Metal
120V	1P+N+G	26-21165-XXX	26-26165-XX
125V	1P+N+G	26-21075-XXX	26-26075-XX
208V	2P+G	26-21162-XXX	26-26162-XX
208V	3P+G	26-21163-XXX	26-26163-XX
208V	3P+N+G	26-21167-XXX	26-26167-XX
250V	2P+G	26-21072-XXX	26-26072-XX
250V	3P+G	26-21073-XXX	26-26073-XX
250V	2P+N+G	26-21076-XXX	26-26076-XX
277V	1P+N+G	26-21045-XXX	26-26045-XX
480V	2P+G	26-21042-XXX	26-26042-XX
480V	3P+G	26-21043-XXX	26-26043-XX
480V	3P+N+G	26-21047-XXX	26-26047-XX
600V	3P+G	26-21143-XXX	26-26143-XX

For international configurations (IEC/CE) visit [meltric.com/international-catalog](http://meltric.com/international-catalog) or contact customer service at 800-433-7642.

## Connector (female recept w/handle)



## Receptacle on box (female)



or

## Receptacle (female)



or

## North American Configurations

Voltage	Polarity	Part #		
		Metal	Metal	Metal
120V	1P+N+G	26-23165-XXX	26-20165-XX	26-24165
125V	1P+N+G	26-23075-XXX	26-20075-XX	26-24075
208V	2P+G	26-23162-XXX	26-20162-XX	26-24162
208V	3P+G	26-23163-XXX	26-20163-XX	26-24163
208V	3P+N+G	26-23167-XXX	26-20167-XX	26-24167
250V	2P+G	26-23072-XXX	26-20072-XX	26-24072
250V	3P+G	26-23073-XXX	26-20073-XX	26-24073
250V	2P+N+G	26-23076-XXX	26-20076-XX	26-24076
277V	1P+N+G	26-23045-XXX	26-20045-XX	26-24045
480V	2P+G	26-23042-XXX	26-20042-XX	26-24042
480V	3P+G	26-23043-XXX	26-20043-XX	26-24043
480V	3P+N+G	26-23047-XXX	26-20047-XX	26-24047
600V	3P+G	26-23143-XXX	26-20143-XX	26-24143

For international configurations (IEC/CE) visit [meltric.com/international-catalog](http://meltric.com/international-catalog) or contact customer service at 800-433-7642.