

PN7c Multipin Plugs & Receptacles – 15 A

Ratings

- **Voltage**
480 VAC Max/130 VDC
 - **Amperage Rating**
15 A Current Interrupting
! Capable of handling 4-20mA low current applications
 - **Environmental Ratings**
IP66/IP67 (Poly/Metal)+
 - **Temperature Range**
Min -40°F / Max 140°F
See pg 258 for temps below -15°F.
 - **Wiring Capacity**
Min 18 AWG Max 10 AWG
 - **Certifications**
UL*, CSA*
- + Does not apply to stainless steel version.

Receptacle (female)



Inlet (male)



! Don't forget to add installation accessories to your order

North American Configurations

Voltage	Polarity	Part #			Part #		
		Poly	Metal	Stainless Steel	Poly	Metal	Stainless Steel
480V	4P+G	01-P4041	09-P4041	09-04041-SS	01-P8041	09-P8041	09-08041-SS
480V	5P+G	01-P4051	09-P4051	09-04051-SS	01-P8051	09-P8051	09-08051-SS
480V	6P+G	01-P4061	09-P4061	09-04061-SS	01-P8061	09-P8061	09-08061-SS

For international configurations and ratings (IEC,CE) visit meltric.com/international-catalog or contact customer service at 800-433-7642.

Main Options



Reverse Interiors



Flush Mount
(replaces female casing)



Locking Pawl

Receptacle Options

Suffix

Inlet Options

Suffix

Reverse Interiors

Recept # - 001

Reverse Interiors

Inlet # - 001

With Flush Mount (poly only)

Recept # - 142*

Locking Pawl (poly/metal only)

Recept # - 824-300

* IP55 rating with Flush Mount casing



See pages 233-242 for detailed information on these options

Order Example: 600V PN7c + Reverse Interiors

PN7c Receptacle 5P+G = 01-P4051-**001**

INSTALLATION ACCESSORIES – SIZE 1

Unless indicated otherwise, accessories can be used with either poly or metal plugs and receptacles. Stainless steel devices should use stainless steel accessories.

HANDLES

HANDLE w/NPT		Part # Poly	Part # Metal
	1/2"	511P0N05	591P0N05
	3/4"	511P0N07	591P0N07
	1"	511P0N10	591P0N10

For available cord grips, see page 167.

POLY HANDLE w/CORD GRIP	Cable Range	Part #
	.350 - .520"	711P0BP6
	.520 - .680"	711P0CP5
	.680 - .980"	711P0DP4

METAL HANDLE w/CORD GRIP		
	.438 - .500"	791P0BS3
	.500 - .562"	791P0BS4
	.562 - .625"	791P0CS1
	.625 - .750"	791P0CS4
	.750 - .875"	791P0DS1
	.875 - 1.000"	791P0DS3

POLY 90° HANDLE w/NPT		
	1/2"	751P9N05
	3/4"	751P9N07
	1"	751P9N10

STAINLESS STEEL HANDLE w/NPT		
	1/2"	7X1P0N05
	3/4"	7X1P0N07

For Stainless Steel devices only. For 1/2" NPT size, a hole size reducer is utilized.

POLY HANDLE		
	.35 - .70"	511P0D18

POLY ANGLED HANDLE		
	.35 - .70"	511P6D18

ANGLES

POLY ANGLE			
	MB Box 30°	511M3	
	70°	511M7	

Panel mounting only.

METAL ANGLE		
	0°	591M0

	FS/FD Box 30°	791M3FS	* Base measures approximately 4.2" x 2.7". Due to the variation in sizes of FS boxes, please verify that your FS box matches our dimensions, if not call Customer Service for other solutions.
	45°	591M4	

	45°	591M4
---	-----	-------

STAINLESS STEEL ANGLE		
	30°	7X1M4

For Stainless Steel devices only.

BOXES

POLY CONDUIT ENTRY w/NPT				Part #
	30°	1/2"		511B3N05
	* 7.0 in ³	30°	3/4"	511B3N07

* Interior volume with receptacle installed.

POLY WALL BOX w/NPT				Part #
	0°	1/2"		511B0N05
	* 3.4 in ³	0°	3/4"	511B0N07

* Interior volume with receptacle installed.

METAL WALL BOX w/NPT				Part #
	0°	1/2"		591B0N05
	* 3.8 in ³	0°	3/4"	591B0N07

* Interior volume with receptacle installed.

POLY WALL BOX w/ANGLE				Part #
	70°			511C7000
	* 82.0 in ³			
	Ground Bar			51AA089

70° poly boxes are not drilled. Contact Customer Service if factory drilled is required.

* Interior volume with receptacle installed.

METAL BOX w/NPT				Part #
	0°	1/2"		7T1F0N05
	0°	3/4"		7T1F0N07
	0°	1"		7T1F0N10
	0°	1 1/4"		7T1F0N12

POLY ANGLE WITH METAL BOX w/NPT				Part #
	30°	1/2"		711C3N05
	30°	3/4"		711C3N07
	30°	1"		711C3N10
	* 30.0 in ³	30°	1 1/4"	711C3N12

* Interior volume with receptacle installed.

METAL ANGLE WITH METAL BOX w/NPT				Part #
	45°	1/2"		791C4N05
	45°	3/4"		791C4N07
	45°	1"		791C4N10
	* 27.0 in ³	45°	1 1/4"	791C4N12

STAINLESS STEEL BOX WITH STAINLESS STEEL ANGLE w/NPT				Part #
	30°	3/4"		7X1C3N07
	30°	1"		7X1C3N10

* Includes angle adapter as shown. For Stainless Steel devices only.

NPT on top or bottom (if rotated). For other NPT configurations, contact Customer Service.

MISCELLANEOUS ACCESSORIES

PROTECTIVE INLET/PLUG CAP		
	01-NA426	For Inlets/Plugs Only.

FLUSH MOUNT		
	01-2A142	

CORD GRIP with MESH		
	see pg 167	