

FLEXIBLE HOOK-UP WIRE / APPLIANCE WIRE

105°C Dry. 75°C Moisture Resistant. 600/1000 Volts. Flexible Stranded Copper Conductor. PVC Insulation.



Images not to scale and for reference only. See Table 1 for Dimensions

ROYAL
WHOLESALE ELECTRIC
SANTA ANA

CONSTRUCTION:

- Conductors: Flexible stranded bare copper; See Table 1 for Stranding Details
Insulation: Polyvinyl Chloride (PVC)
Colors: All Colors available; Stripes available upon request in 4/0 AWG and smaller sizes.

APPLICATIONS AND FEATURES:

For use in internal wiring of electrical equipment, control panels, appliances, and grounding for use on industrial plan floor.
For use as permitted in NEC Article 310 and NFPA #79. For use in boat wiring in accordance with 33 CFR 183.425 - 435.

SPECIFICATIONS:

- ASTM B3
- UL 758 - Appliance Wire
 - AWM 1011/1015/1032/1230/1335 - 22 - 10 awg
 - AWM 1011/1028/1032/1230/1344 - 8 awg
 - AWM 1232/1283/1346/10269; 6 - 2 AWG
 - AWM 1232/1284/1338/10269; 1 - 4/0 AWG
 - AWM 1284/1339/10269; 250 kcmil - 500 kcmil
- Voltage: 600V, AWM 10269 - 1000V
- UL 83 - Type THHW; 90°C Dry, 75°C Wet
- UL 1063 - Machine Tool Wiring (MTW); 90°C Dry, 60°C Wet/Oil
- UL 1426 - BC-5W2; Sizes - 16 to 4/0 AWG; 105°C Dry, 75°C Wet

ADDITIONAL SPECIFICATIONS:

- CSA C22.2 No. 127 - Type TEW; Sizes 22 - 4/0 awg; 105°C Dry
- CSA C22.2 No. 210 - AWM I A/B; 105°C Dry
- Oil Res I
- Sun Res - 8 AWG & larger sizes
- For CT Use - 1/0 AWG & larger sizes
- RoHS-2 Compliant

SAMPLE PRINT LEGEND:

18 AWG (0.823mm2) E51583 (PLANT ID CODE) (UL) MTW OR AWM 1011/1015/1230/1335/1345 600V OR 1032 1000V
MOISTURE RESISTANT VW-1 -- 156205 CSA TEW 105C 600V FT1 OR AWM I A/B 105C 600V FT1

SAMPLE PRINT LEGEND:

8 AWG (8.37mm2) E69567 (PLANT ID CODE) (UL) BC-5W2 OR MTW OR THHW OR AWM 1011/1028/1231/1344 600V OR 1032
1000V MOISTURE RESISTANT OIL RES I SUN RES VW-1 -- 156205 CSA TEW 105C 600V FT1 OR AWM I A/B 105C 600V FT1

SAMPLE PRINT LEGEND:

2 AWG (33.6mm2) E69567 (PLANT ID CODE) (UL) BC-5W2 OR MTW OR THHW OR AWM 1232/1283/1346 600V OR 10269
1000V OIL RES I SUN RES VW-1 -- 156205 CSA TEW 105C 600V FT1 OR AWM I A/B 105C 600V FT1 -- SAE J1127 TYPE SGT



Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | www.southwire.com

Copyright © 2016 Southwire Company, LLC. All Rights Reserved



Southwire®

FLEXIBLE HOOK-UP WIRE / APPLIANCE WIRE

TABLE 1 - WEIGHTS & MEASUREMENTS

Stock Code	Cond. Size (AWG/Kcmil)	Number of Strands	Nominal Insulation Thickness (inches)	Nominal OD (inches)	Nominal Weight (Lbs/Mft)
Rated: AWM Styles 1011/1015/1032/1230/1335; UL MTW; CSA TEW & AWM					
F22023	22	7	0.030	0.091	5.5
F20033	20	10	0.030	0.099	7.2
F18043	18	16	0.030	0.106	9.3
Rated: AWM Styles 1011/1015/1032/1230/1335; UL BC-5W2 & MTW; CSA TEW & AWM					
F16027	16	26	0.030	0.117	13
Rated: AWM Styles 1011/1015/1032/1230/1335; UL BC-5W2, MTW, & THHW; CSA TEW & AWM					
F14032	14	41	0.030	0.132	19
F12022	12	65	0.030	0.155	27
F10010	10	105	0.030	0.175	39
Rated: AWM Styles 1283/1232/1346/10269; UL BC-5W2, MTW, & THHW; CSA TEW & AWM					
F08008	8	133	0.045	0.252	70
Rated: AWM Styles 1283/1232/1346/10269; UL BC-5W2, MTW, & THHW; CSA TEW & AWM					
F06005	6	133	0.060	0.324	116
F04053	4	133	0.060	0.387	164
F02049	2	133	0.060	0.452	256
Rated: AWM Styles 1284/1232/1338/10269; UL BC-5W2, MTW, & THHW; CSA TEW & AWM					
F01028	1	133	0.060	0.535	323
F1T043	1/0	259	0.080	0.561	401
F2T040	2/0	259	0.080	0.625	484
F3T034	3/0	259	0.080	0.666	605
F4T029	4/0	259	0.080	0.735	812
Rated: AWM Styles 1284/1339/10269; UL MTW & THHW; CSA AWM					
F25006	250	2451	0.095	0.835	934
51535	350	3458	0.095	0.930	1268
51540	400	3990	0.095	0.985	1421
51550	500	5054	0.095	1.080	1770
Rated: AWM Styles 1284/1340/10269; UL MTW & THHW; CSA AWM					
51478	750	7585	0.110	1.336	2620

All dimensions are nominal and subject to nominal manufacturing tolerances



Electrical distributor of high
quality products to the LA and
Orange County markets

Call Us Today
To get a Quote



(714) 835-6211

sales@royalsantaana.com



Southwire Company, LLC | One Southwire Drive, Carrollton, GA 30119 | www.southwire.com

Copyright © 2016 Southwire Company, LLC. All Rights Reserved



Southwire®